

# WALLTITE® One Closed-cell Spray Foam One Insulation. Multiple Applications.





WALLTITE<sup>®</sup> One is a high-performance, medium-density, HFO-based closed-cell SPF insulation designed for smooth, effortless application while meeting GREENGUARD Gold standards and other rigorous requirements. Ideal for insulation and air sealing in residential and commercial construction, WALLTITE One offers consistent thermal performance, lower viscosity for easier spraying, and reduced clogging for a long, efficient spray time-frame. It provides contractors with reliable yield and superior, hassle-free application year-round.

# PERFORMANCE MADE SIMPLE

#### **Effortless Application**

- Consistent Performance Year-Round: Exceptional spray consistency, even in challenging winter conditions.
- No Hassle, Plug-and-Go: Balanced reactivity ensures minimal adjustments.
- Wide Application Window: A forgiving processing range generates high-quality results with less effort.

### **Superior Workability**

- Lower Viscosity: Less effort and easier application at lower temperatures.
- **Equipment efficiency:** Reduced gun clogs means longer, more efficient spray time.

#### **Increased Efficiency**

- **Minimal Adjustments Needed:** Simplifies the spraying process with less time spent fine-tuning settings.
- **Consistent, High-Quality Finish:** Provides smooth surface texture with minimal effort, reducing touch-ups.
- **Fast installation:** High lift (up to 3.5" single pass) and back-to-back applications (3.5"+3.5") with no dwell time required allows maximum efficiency on projects.

# **MORE PRODUCT FEATURES & QUALIFICATIONS**

- GREENGUARD Gold certification
  Documented low-VOC material for improved IAQ
- Quick re-entry time - 2 hours for other trades with proper ACH
- Low-GWP, HFO-based formulation
- Superior efficiency: R-values from 7.2 to 7.5 per/in
- NFPA 285 compliant assemblies available
- UL 263 Fire Resistance Rated assemblies available
- Intertek Code Compliance Research Report (CCRR-0374)
- UL Solutions Environmental Claim Validation (ECV) for mold-resistance
- UL Solutions ECV for bio-content and recycled content (pending)







1-888-900-FOAM SPFinfo@basf.com

#### Spray Foam Technical Application Support 800-706-0712, Ext 2 SPF.techsales@basf.com

BASF Corporation Houston, TX 77054 <u>spf.basf.com</u>

Data presented in this document is based on tests and information, which we believe to be reliable. This document is provided for information purposes only and without any representation, warranty or condition, expressed or implied, regarding its accuracy or completeness. Whether or not this data is used or relied upon is within the sole discretion and judgement of user. Since BASF Corporation has no control over the conditions of handling, storage, use and disposal of the products, BASF Corporation does not assume any responsibility or liability and expressly disclaims all liability for any claim, loss, damage, injury or expense resulting therefrom.

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Because many factors may affect processing or application/use, BASF recommends that the reader make tests to determine the suitability of a product for a particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered a part of the BASF terms and conditions of sale. Further, the descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the description, designs, data or information given or results obtained, all such being given and accepted at the reader's risk.

UL and the UL logos are trademarks of UL LLC. WALLTITE® is a registered trademark of BASF Corporation. ©2025 BASF Corporation

